

0353030.052204

1
1
2
3
4
5
6

1
2

1
2

1
2

1
2

1
2

1
2

1
2

1
2

1
2
3

WHAT IS CLAIMED IS

1. A communications network comprising:
a source node;
a destination node;
at least one airborne intermediary node located aboard an aircraft and
including a router for routing a message between said source node and said destination node
using one of a VHF or UHF frequency.
2. The communications network of claim 1 wherein said source node is
located on the ground.
3. The communications network of claim 1 wherein said destination node
is located on the ground.
4. The communications network of claim 1 wherein said source node is a
second aircraft.
5. The communications network of claim 1 wherein said destination node
is a second aircraft.
6. The communications network of claim 1 wherein said message is a
data message.
7. The communications network of claim 1 wherein said message is a
voice communications message.
8. The communications network of claim 1 wherein said message is a
broadband data message.
9. A method for telecommunications comprising the steps of:
receiving at an intermediary node located aboard an aircraft, a request message
transmitted from a source node;

4 transmitting a modified request message from said intermediary node
5 including information about said second node;

6 receiving at said intermediary node, an acknowledgment message transmitted
7 from a destination node; and

8 retransmitting said acknowledgment message from said intermediary node to
9 said source node, whereby a circuit is established for routing a data message between said
10 source node and said destination node via said intermediary node.

1 10. The method of claim 9 wherein said steps of transmitting and
2 retransmitting include the step of transmitting on a VHF frequency.

1 11. The method of claim 9 wherein said steps of transmitting and
2 retransmitting include the step of transmitting on an UHF frequency.

1 12. The method of claim 9 wherein said data message is a voice
2 communications message.

1 13. The method of claim 9 wherein said data message is a broadband data
2 message.

1 14. A method for telecommunications comprising the steps of:
2 receiving a message at an antenna located aboard an aircraft;
3 inputting said message to a signal processing device to determine if said
4 message is destined for said aircraft; and

5 retransmitting said message from said aircraft when said message is destined
6 for other than said aircraft.

1 15. The method for telecommunications of claim 14 wherein said step of
2 retransmitting said message further comprises the step of transmitting on a VHF frequency.

1 16. The method for telecommunications of claim 14 wherein said step of
2 retransmitting said message further comprises the step of transmitting on an UHF frequency.

1 17. The method for telecommunications of claim 14 wherein said step of
2 inputting said message to a signal processing device further comprises the steps of:

2 a fourth computer instruction means for determining if communications can be
3 maintained with a node from which said message was received during a predefined time
4 interval.

1 23. The computer program product of claim 21 further comprising:

2 a fourth computer instruction means for determining if communications can be
3 maintained during a predefined time interval with a node within reception range of said
4 aircraft transmitter.

1 24. The computer program product of claim 23 further comprising:

2 a fifth computer instruction means for reading an aircraft position information.

1 25. The computer program product of claim 22 further comprising:

2 a fifth computer instruction means for reading an aircraft position information.

1 26. The computer program product of claim 21 further comprising:

2 a fourth computer instruction means for writing said message to a local
3 distribution subsystem for routing said message to a system aboard said aircraft.

1 27. An apparatus for routing messages in a telecommunications network
2 comprising:

3 an input for inputting a message received at an antenna located aboard an
4 aircraft;

5 an output; and

6 a signal processing device, coupled to said input and to said output, for:

7 determining if said message is destined for said aircraft;

8 outputting said message to a first storage device coupled to an aircraft
9 transmitter when said message is destined for other than said aircraft; and

10 outputting said message to a second storage device coupled to a local message
11 distribution system when said message is destined for said aircraft.

1 28. The apparatus of claim 27 wherein said signal processing device
2 comprises a general purpose processor.

29. The apparatus of claim 27 wherein said signal processing device comprises a router.

30. The apparatus of claim 27 wherein said input is further adapted to receive signals indicative of aircraft position and wherein said signal processor determines if communications can be maintained during a predefined time interval with a communications node within reception range of said aircraft transmitter.

31. A computer program product for telecommunications comprising:
a computer readable storage medium having computer readable program code means embodied in said medium, said computer readable program code means comprising:

a first computer instruction means for reading a request message transmitted from a source node and received at an antenna located aboard an aircraft;

a second computer instruction means for writing a modified request message including data about said aircraft to a storage device coupled to an aircraft transmitter;

a third computer instruction means for reading an acknowledgment message transmitted from a destination node in response to broadcast of said modified request message; and

a fourth computer instruction means for writing a modified acknowledgment message including said data about said aircraft to said storage device for transmission from said aircraft and whereby a circuit is established for routing a data message between said source node and said destination node via said aircraft.

32. The computer program product of claim 31 further comprising:
a fifth computer instruction means for reading an aircraft position information.

33. The computer program product of claim 32 further comprising a sixth computer instruction means for predicting if communications over said circuit can be maintained during a predefined time interval.

34. An apparatus for routing messages in a telecommunications network comprising:

3 an input;
4 an output; and
5 a signal processing device, coupled to said input and to said output, for:
6 reading a request message transmitted from a source node, received at an
7 antenna located aboard an aircraft and provided to said input;
8 outputting a modified request message including data about said aircraft;
9 reading an acknowledgment message transmitted from a destination node in
10 response to a broadcast of said modified request message; and
11 outputting a modified acknowledgment message including said data about said
12 aircraft for transmission from said aircraft whereby a circuit is established for routing a data
13 message between said source node and said destination node via said aircraft.

1 35. The apparatus of claim 34 wherein said signal processing device
2 comprises a general purpose processor.

1 36. The apparatus of claim 34 wherein said signal processing device
2 comprises a router.

1 37. The apparatus of claim 34 wherein said input is further adapted to
2 receive signals indicative of aircraft position and wherein said signal processor determines if
3 communications can be maintained during a predefined time interval with a communications
4 node within reception range of said aircraft transmitter.

1 38. A telecommunications network architecture comprising:
2 a source node;
3 a destination node; and
4 a plurality of airborne aircraft, each airborne aircraft having a radio
5 transmit and receive capability, for routing a packet data between said source node and said
6 destination node via said plurality of airborne aircraft.

1 39. The telecommunications network of claim 38 wherein said source node
2 is an aircraft.

1 40. The telecommunications network of claim 38 wherein said destination
2 node is an aircraft.

1 41. The telecommunications network of claim 38 wherein at least one of
2 said source node or said destination node is a groundbased network.

1 42. The telecommunications network of claim 38 wherein said transmit
2 and receive capability includes a VHF transmit and receive capability.

1 43. The telecommunications network of claim 38 wherein said transmit
2 and receive capability includes an UHF transmit and receive capability.